




383

Earth Lead Adaptor (Male to Female)



General Information

- Manufactured in Brass, Nickel Plated Brass and Stainless Steel.
- PVC Insulated Cable as standard, (Optional LSOH cable).
- M20 to M75 as standard, other thread forms available on request.
- Different thread sizes and types are permitted each end of the adaptor. The thread sizes may differ by one size only.
- If longer cable lengths than standard are required, advise length in millimeters.
- Suitable for use in Zone 1, Zone 2, Zone 21 and Zone 22.
- Construction and Test Standards: IEC/EN 60079-0, IEC/EN 60079-7 and IEC/EN 60079-31.
- Ingress Protection: IP66. (when installed with a Hawke washer)
- Assembly Instruction Sheet: AI 413.

Certification Details

- Increased Safety Exe IIC Gb, Extb IIIC Db, II 2GD.
- Certificate No's: Baseefa 11ATEX0152X and IECEx BAS 11.0074X.
- Ex TC RU C-GB.ГБ05.В.00750 EAC
- Operating Temperature Range -60°C to +80°C.
- Group II and III.

Selection Table

Thread Size Male / Female	Across Flats (mm)	Across Corners (mm)	Cable Length (mm)	Cable Size (sq. mm)
M20 / M20	24	26.5	250	4
M25 / M25	30	32.5	250	4
M32 / M32	36	39.5	250	6
M40 / M40	46	50.5	250	10
M50 / M50	55	60.5	500	16
M63 / M63	70	77.5	500	25
M75 / M75	80	88	500	25

Ordering Information

Product	Thread Size	Material	Finish
383	M32 Male x M32 Female	Brass	Nickel Plated

Note: Always state the male thread first



389

Breather Drain & Locknut



General Information

- Manufactured in Brass, Nickel Plated Brass, Stainless Steel – Grade 316L. O Ring manufactured from Silicone Rubber.
- M20 and M25 with 1.5mm pitch as standard.
- Longer thread lengths are available on request.
- Suitable for use in Zone 1, Zone 2, Zone 21, Zone 22 and mining applications.
- Construction and Test Standards: IEC/EN 60079-0, IEC/EN 60079-7 and IEC/EN 60079-31.
- Ingress Protection: IP66.
- Assembly Instruction Sheet: AI 408.

Certification Details

- Increased Safety Exe I Mb, Exe IIC Gb, Extb IIIC Db, I M2 / II 2GD.
- Certificate No's: Baseefa 11ATEX0153X and IECEx BAS 11.0075X.
- Ex TC RU C-GB.ГБ05.В.00750 EAC
- Operating Temperature Range:
Nitrile 'O' Ring fitted as standard -60°C to +80°C
Silicone Option -60°C to +160°C
- Group I, II and III.

Selection Table

Thread Size	Length of Thread (mm)	Across Flats (mm)	Across Corners (mm)
M20	15	30	32.5
M25	15	36	39.5

Ordering Information

Product	Thread Size	Pitch	Material	Finish
389	M25	1.5 mm	Brass	Nickel Plated