



LUNA LED

HDL106TN Transportable Ex e LED Floodlight

The **Luna** Floodlight is an easily portable, reliable and highly powerful luminaire that directs a crisp, targeted output (up to 5,600lm) where you need it most.

With a robust, marine grade construction, maintenance-friendly design and LED lifespan of over 10 years, the **Luna** is ideal for temporary lighting applications



International Approvals



Standard Specification

HDL106TN Transportable Ex e LED Floodlight

Type of Protection	Ex e mb (Increased Safety, Encapsulation) Ex tb (Dust Protected Enclosure)
ATEX Classification	Group II Category 2 GD
Area Classification	Zone 1 and 21 areas to EN 60079-10-1 and EN 60079-10-2 with installation to EN 60079-14
Certificate	EU Type Examination Certificate Sira 10ATEX5115X IECEX Certificate of Conformity IECEX SIR 10.0055X
Coding	Ex e mb IIC T* Gb Ex tb IIIC T*** °C Db Refer to table for T rating and Ambient
Enclosure	LM6 Aluminium with yellow epoxy powder finish (RAL 1018) and Polycarbonate diffuser
Entry	2 x M20 cable entries
Termination	3 core 4mm ² max. conductor with looping
Installation	Stirrup mounted within transportable frame
Control Gear	Electronic Driver
Optical Distribution	Wide beam (50°)
Colour Temperature (CCT)	5000K (Cool White)
Colour Rendering Index (Ra)	>70
Maintenance	M8 Hex Head and M6 SKT Head
LED Lifetime @ 25°C Ambient	L70 > 150,000hrs
Impact Protection	IK10
Ingress Protection	IP66/67 to EN 60529
Surge Protection	4kV line to line, 6kV line to earth
Electrical Supply	Refer to Ordering Matrix (For details on Transformers or Splitter Boxes, please contact Internal Sales)

Features

- ◆ **Ultra bright light** with market-leading efficacy
- ◆ **9kg Lightweight** transportable floodlight
- ◆ **>150,000 maintenance free hours** at 25°C (L70)
- ◆ Available with a **variety of cable lengths and plugs**
- ◆ **Robust marine grade construction** designed for tough use
- ◆ **Independent LED engines** for ultimate reliability and confidence on site*

*48 LED option only

Std. Cat No.	Delivered Output	Power Consumption	Voltage	Tclass	T °C (Dust)	Ambient °C	Weight
HDL106TN0HWHW006	2812lm	27W	100-254V AC	T4 T3	103	-20 to +50 -20 to +55	9kg
HDL106TN0LWHW006	2812lm	27W	18-54V AC/DC	T4	87	-20 to +55	9kg
HDL106TN1HWHW006	5624lm	53W	100-254V AC	T4 T3	103	-20 to +50 -20 to +55	9kg
HDL106TN1LWHW006	5624lm	53W	18-54V AC/DC	T4	87	-20 to +55	9kg

Options - Suffix to Catalogue No.

FG Flat Glass and Aluminium front cover **BP** Nickel plated brass plugs (not available with Linkable version)

HDL106TN CABLING CONFIGURATOR

Plug Manufacturer**	Plug Voltage**	Cable Type	Cable - Length	Linkable
C - CEAG	024 - 24V	S - SY Armoured	05 - 5m cable	L - Linkable version*
A - ATX	110 - 110V	H - H07RN-F rubber	10 - 10m cable	
S - STAHL	230 - 230V		15 - 15m cable	

Typical ordering reference: **HDL106TN1HWHW006-C230H15**

*Ambient restrictions apply when linking multiple units with CEAG sockets. Please contact Chalmit Technical for further information.

**If a plug is not required, please leave Manufacturer and Voltage blank, e.g. HDL106TN1HWHW006-H15

